

Loose lay design floorcovering with PUR surface coating

EXPONA SIMPLAY

1. GENERAL INFORMATION

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the floorcovering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floorcovering, will be compromised.

EXPONA SIMPLAY incorporates a polyurethane (PUR) surface treatment, which protects the floorcoverings by resisting soiling. This protection facilitates the maintenance and provides the foundation for the ongoing maintenance regime.

2. PREVENTATIVE MEASURES

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats. The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least four to six paces wide.

3. INITIAL CONSTRUCTION CLEAN

After laying, a final construction cleaning is to be carried out. All contamination and residue caused by production is completely removed here with a neutral or PU cleaner.

Please use cleaning detergents sparingly (wipe with a slightly damp applicator).

4. APPLICATION OF A FLOORDRESSING

It is not necessary to apply such a protection to objectflor floorcoverings with a PUR surface treatment as this treatment will provide permanent protection.

5. ROUTINE MAINTENANCE

Daily

Mop sweep or vacuum the floor to remove dust and loose dirt. Stubborn marks should be removed using a neutral or a PU cleanser. If required, dry buff with a single-disc machine and a white pad.

Damp mop

Thanks to a 2-step mopping system with double wheeled bucket, good cleaning results are obtained.

6. PERIODICALLY

It may become necessary to remove stubborn marks from time to time by using a neutral or a PU detergent according to the manufacturers' instructions.

Please use cleaning detergents sparingly (wipe with a slightly damp applicator).

7. REMOVAL OF POLISH

A thorough clean may be necessary from time to time, if ongoing general cleaning is no longer producing a satisfactory result or the surface has been damaged by excessive abrasive wear (soiling with sand/grit, sharp-edged items) on the same sections of the surface.

The floor should then be scrubbed using a mono-pad rotary machine (green pad) or a scrubber and the slurry should be removed completely. Neutralise the floor with clean water. Then re-apply a floor dressing (polish of the polymer dispersion type or of the PU sealing type).

Please heed the recommendations of the cleaning agent manufacturer.

IMPORTANT NOTES

For hairdresser salons, car dealers

Substances with a colouring or bleaching effect must be removed immediately from the covering, in order to avoid any lasting impairment to the appearance. It is possible to coat the floorcovering with an additional 2 component PU sealer to protect against stains.

For the health service

In areas where palm and skin disinfectants are used, we recommend an additional treatment with suitable polymer dispersion or PU sealing product before the first use.

For strongly frequented areas and surfaces

In areas which are expected to be highly frequented, e.g. shops, entrances, receptions etc., we recommend applying a suitable PU sealing product before first use.

Additional treatment with a PU sealing system will unavoidably cause the edges of the elements to become bonded to each other.

General information

Please use cleaning detergents sparingly (wipe with a slightly damp applicator).

When using wheeled chairs, double swivel rollers are to be used (soft type). The contact areas of mobile furniture should be equipped with suitable felt or soft plastic bearings.

When selecting cleaning and maintenance products and the mechanics used, ensure that these are adapted to one another and consider the manufacturer's notes.

For further guidance contact objectflor Customer Technical Support or visit our homepage: www.objectflor.de