

EXPONA DESIGN flooring is a heterogeneous PVC floor covering which is produced using phthalate-free and bio-based plasticisers, designed for use in areas with very heavy commercial areas.

Characteristics	Standards	Unit	EXPONA DESIGN
Type of floor covering	EN ISO 10582		heterogeneous, PVC
Surface treatment			PUR
Colours			42
Total weight	EN ISO 23997	g/m ²	5100
Performance classification	EN ISO 10874		23 34 43 **
Gauge	EN ISO 24346	mm	3,0
Wear layer thickness	EN ISO 24340	mm	0,7
Packaging tile, plank size	EN ISO 24342	mm	12 @ 304,8 x 914,4 = 3,34 m ² 16 @ 457,2 x 457,2 = 3,34 m ² 8 @ 457,2 x 914,4 = 3,34 m ² 9 @ 609,6 x 609,6 = 3,34 m ² 6 @ 609,6 x 1219,2 = 4,46 m ² 6 @ 914,4 x 914,4 = 5,01 m ² 24 @ 152,4 x 914,4 = 3,34 m ² 18 @ 152,4 x 1219,2 = 3,34 m ² 15 @ 184,2 x 1219,2 = 3,37 m ² 12 @ 184,2 x 1524,0 = 3,37 m ² 14 @ 203,2 x 1219,2 = 3,46 m ² 11 @ 203,2 x 1524,0 = 3,41 m ²
Dimensional stability	EN ISO 23999	%	≤ 0,1 ***
Residual indentation	EN ISO 24343-1	mm	≤ 0,05 ***
Colour fastness to artificial light	EN ISO 105-B02	level	≥ 6
Behaviour to fire	EN 13501-1		B _{fl} - s1
Slip resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann B		Class DS R10
Impact sound reduction	EN ISO 10140-3	dB	3
Thermal conductivity	EN 12524	W m/K.	0,25
Assessment of static electrical propensity	EN 1815	kV	≤ 2, antistatic
Chemical resistance	EN ISO 26987		*
Abrasion group	EN ISO 10582		binder content type I
Castor chair suitability	ISO 4918		yes, type W, EN 12529
Underfloor heating suitability	EN 1264-2		suitable, max. 27 °C
VOC emissions	Indoor Air Comfort GOLD Floorscore Finnish M1 Classification AgBB VOC test		Eurofins certified product certified pass very low emissions
Environmental product declaration	EN 15804 fDES EPD		DGNB Navigator / www.dgnb-navigator.de SFEC / www.solspvcpro.com
CE	EN 14041		



* Resistant depending on concentration and time of exposure, in case of increased impact of oils, grease, acids, alkalis and other aggressive chemicals – please contact us.

** Heavy rolling loads to be avoided

*** Averaged test value from current production

Subject to change due to further technical development.